

# MULTIPURPOSE



2.0MPa / 300PSI (100% rubber hose) – 10.1215.

Oil, Fuel and Gasoline

REFERENCE	#	inch	SAE Dash	ID mm	OD mm	MPa	PSI	MPa	PSI	MIN BEND RAD mm	KG kg/m
MULTI-03	10.1215.03	3/16"	-3	4,8	11,0	<b>2,0</b>	300	<b>6,0</b>	1200	50	0,10
MULTI-04	10.1215.04	1/4"	-4	6,3	12,8	<b>2,0</b>	300	<b>6,0</b>	1200	60	0,16
MULTI-05	10.1215.05	5/16"	-5	8,0	14,9	<b>2,0</b>	300	<b>6,0</b>	1200	80	0,24
MULTI-06	10.1215.06	3/8"	-6	9,5	16,7	<b>2,0</b>	300	<b>6,0</b>	1200	100	0,29
MULTI-08	10.1215.08	1/2"	-8	12,7	21,0	<b>2,0</b>	300	<b>6,0</b>	1200	125	0,40
MULTI-10	10.1215.10	5/8"	-10	16,0	24,2	<b>2,0</b>	300	<b>6,0</b>	1200	160	0,50
MULTI-12	10.1215.12	3/4"	-12	19,0	28,0	<b>2,0</b>	300	<b>6,0</b>	1200	190	0,66
MULTI-16	10.1215.16	1"	-16	25,4	35,0	<b>2,0</b>	300	<b>6,0</b>	1200	254	0,90
MULTI-20	10.1215.20	1 1/4"	-20	32,0	42,8	<b>2,0</b>	300	<b>6,0</b>	1200	320	1,20
MULTI-24	10.1215.24	1 1/2"	-24	38,0	49,8	<b>2,0</b>	300	<b>6,0</b>	1200	380	1,42
MULTI-32	10.1215.32	2"	-32	50,8	62,2	<b>2,0</b>	300	<b>6,0</b>	1200	510	1,89

**INNER TUBE:** seamless oil, fuel and gasoline resistant synthetic rubber

**REINFORCEMENT:** 1 high resistance synthetic fiber braid

**SAFETY FACTOR:** 3:1

**OUTER TUBE:** black wrapped, weather and abrasion resistant synthetic rubber

**APPLICATION:** oil, fuel and gasoline

**TEMPERATURE RANGE:** -40°C (-40°F) +100°C (+212°F); Max. temperature recommended for water base hydraulic fluids: +70°C (+158°F); Max. temperature recommended for air: +50°C (+122°F)

**COVER:** U.S. MSHA APPROVED

**WARNING:** this hose is not according to any particular standards, so should not be used in automotive applications

 **BALFLEX // MULTIPURPOSE** OIL - FUEL - AIR - GASOLINE - DN5 - 3/16" - WP <sup>2 MPa</sup> <sub>300 PSI</sub> - Flame Resistant - MSHA IC-252/00